

RTX150 PEDESTRIAN TRENCHER



20.5 HP (15.3 KW) GAS ENGINE. This unit offers 68% greater torque than lower-powered models that increases digging performance compared to other machines to help get the job done faster.



VZ STEERING. Instead of additional levers and steerable wheels, operators can turn the machine using only the handlebars. These bars also provide additional leverage when operating in difficult terrain.



MASTER OF YOUR TERRAIN. Attain maximum performance and productivity despite varying surface conditions with interchangeable tracks and tires.



NARROW WIDTH. Due to the small size of the machine, it can access small and confined spaces, including maneuvering through typical backyard gates.



LEAVE IT LIKE YOU FOUND IT. This model features an optional backfill blade to aid jobsite restoration.



SET UP FOR STEADY COOLING. The machine is equipped with a heavy-duty hydraulic oil cooler and reservoir to help manage system temperature increasing reliability and performance.



VERMEER.COM



EQUIPPED TO
DO MORE.™

RTX150 PEDESTRIAN TRENCHER

GENERAL DIMENSIONS & WEIGHTS

Length: 81.4" (206.8 cm)

Width (over rubber tracks): 34" (86.4 cm)

Width (over rubber tires): 35" (88.9 cm)

Height: 46" (116.8 cm)

Weight: 1000 lb (453.6 kg)

TRENCHER

Max trench depth: 36" (91.4 cm)

Cutting width: 4" (10.2 cm) - 6" (15.2 cm)

Auger diameter: 16" (40.6 cm)

Auger outboard bearing support: 1.25" (3.2 cm) ID

Chain speed: 320 ft/min (97.5 m/min)

ENGINE

Make and model: Kohler CH20

Gross horsepower: 20.5 hp (15.3 kW)

Displacement: 39.1 cu-in (.624 L)

Fuel type: Gasoline

Fuel tank capacity: 2.8 gal (10.6 L)

Cooling medium: Forced air

Max operating angle (fore/aft/left/right): 25°

HYDRAULIC SYSTEM

Hydraulic tank capacity: 12 gal (45.4 L)

Attachment pump relief pressure: 2975 psi (205 bar)

Ground drive pump relief pressure: 2400 psi (165.5 bar)

Attachment pump gpm at max engine rpm: 10.5 gpm (39.6 L/min)

GROUND DRIVE

Ground drive type: Hydrostatic

Max forward transport speed at full throttle: 3.1 mph (5 km/h)

Max reverse transport speed at full throttle: 1 mph (1.6 km/h)

Steering type: VZ steering system

OPTIONS

Backfill blade

Trench cleaner

Extended warranty

Special paint

Planned maintenance

Vermeer Confidence Plus® Asset Protection Program

NOTES:

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo and Equipped to Do More are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. © 2015 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

