

# PRO WALK-BEHIND TROWELS

PRO SERIES WALKERS



Allen Pro-Series Walkers feature precision engineered gearboxes for long, trouble-free life. We use cast iron spiders, pressure plates and lift levers for long wear and continuous service, and we precision machine our trowel arms and spiders to such close tolerances that our trowels do not require bushings.

## CONTRACTOR TOUGH

SITE PREP • PLACING • FINISHING • PAVING EQUIPMENT

# PRODUCT DETAILS



POWERED by  
**HONDA**



## UNIQUE PATENTED EDGING WALKER

This unique 36" rotating edge ring can only be found on PRO436 E. It is perfect for troweling along the edges of walls or around protruding pipe and conduit.



Fine pitch handles use a twist action to control blade pitch from flat to 28° and anything in between.



Positive pitch handles use a ratcheting action to provide easy adjustment with the push or pull of a lever.

DESCRIPTION	PRO436	PRO436 E	PRO436 P	PRO446	PRO446 TC
ENGINE	Honda GX160 (163 cc)	Honda GX270 (270 cc)	Subaru EX27 (265 cc)	Honda GX270 (270 cc)	Honda GX390 (389 cc)
HORSE POWER CLASS	5.5 hp (4.1 kW) or 9 hp (6.7 kW)	9 hp (6.7 kW)	9 hp (6.7 kW)	9 hp (6.7 kW)	13 hp (9.7 kW)
ROTOR DIAMETER	36 in (92 cm) 4-blades	36 in (92 cm) 4-blades	36 in (92 cm) 4-blades	46 in (117 cm) 4-blades	46 in (117 cm) 4-Blades
MAXIMUM ROTOR SPEED	120 rpm	120 rpm	120 rpm	120 rpm	180 rpm
TROWEL ARMS & SPIDER	Standard Duty	Standard Duty	Standard Duty	Standard Duty	Super Duty
WEIGHT	186 lb (89 kg) or 222 lb (101 kg)	198 lb (89 kg)	275 lb (125 kg)	250 lb (113 kg)	315 lb (142 kg)
DIMENSIONS (L X W X H)	72 x 38 x 36 in (177.8 x 96.5 x 91.5 cm)	84 x 36 x 38 in (213.4 x 91.5 x 96.5 cm)	72 x 38 x 36 in (177.8 x 96.5 x 91.5 cm)	78 x 48 x 39 in (198.1 x 121.9 x 99 cm)	78 x 48 x 39 in (198.1 x 121.9 x 99 cm)