

6-CUFT CLASSIC BLAST MACHINE SYSTEMS

IMPORTANT: For safe, efficient blasting, read and follow the operations manual and seek training for everyone who will use this equipment.



Simple to operate and maintain. Rugged, reliable, and versatile. Loaded with standard features. A blast machine that works as hard as you.

OVERVIEW

Yard-portable, versatile blast machine that removes contamination, corrosion, mill scale, and coatings from most surfaces. It produces a uniform surface texture and creates a surface profile to increase bonding for coatings.

CAPACITY

• Holds 6 cuft of media; 600 lbs of expendable mineral abrasive.

1.25" PIPING

- Provides about 30 minutes of blasting at 100 psi with a No. 6 nozzle.
- Supplies up to 50% more air flow than 1" piping.

PRESSURE VESSEL

 Heavy-gauge vessel meets ASME specifications for 150-psi working pressure.

- Hydrostatically tested and National Board certified.
- Semi-elliptical head provides larger abrasive storage.
- Conical 35° bottom for uninterrupted abrasive flow and complete emptying.

TECHN

0

≻

⊳ ⊢

 $\mathbf{\Sigma}$

S

Т

Ш

Ш

-

۲

• Large 6" x 8" inspection doors eases access to vessel interior.

FSV METERING VALVE

- Smooth, consistent, adjustable media flow.
- Abrasive flows at a 45° angle; eliminates premature wear found in 90° valves.

TLR REMOTE CONTROLS

- Fast, safe pressure-release remotes with solid brass valves for years of dependability.
- Complies with OSHA regulation 1910.244 (b).

POP-UP VALVE

- Urethane-coated with external pressure sleeve for long life and fast pressurization.
- Optional valve umbrella relieves load pressure when hopper is in place.

OTHER COMPONENTS

- Industrial-quality valves, piping, and fittings maximize airflow and minimize energy usage.
- Chrome-plated, forged-brass ball valve with brass body increases durability.
- Flexible pusher line promotes air flow without pressure loss caused by elbows and the hose flexibility eases valve replacement.
- Self-cleaning exhaust muffler greatly reduces bleed-off noise.

Stock No. 24880

 (\bullet)

CLEMCO

10

23

24

26

25

3

14

DIAGRAM KEY

2. Leather Gloves

8. Nozzle Holder 9. TXP-6 Nozzle

12. Twinline Hose

14. Standard Wye

16. Axle and Wheel

18. Inlet Valve

20. Outlet Valve 21. Abrasive Trap 22. Optional Cover

· Conversion kit:

Portable machine

23. Screen

17. Ball Valve Handle

19. Exhaust Muffler

24. Inspection Door Assembly

25. Abrasive Metering Valve

26. Blast Hose Safety Cable

to stationary 30073

13. Coupling

1. Apollo Respirator

3. Respirator Air Flow Device

4. 50' x 3/8" Respirator Hose 5. CALIPSO Ambient Air pump

6. CPF Breathing Air Filter 7. RLX Pneumatic Handle

10. Poly All-Weather Cover

11. 50' Supa Blast Hose

15. Flexible Pusher Line

15

0 ≻ ⊳ - $\mathbf{\Sigma}$ ŝ Т Ш ш -

-1 m 0

Т z



11

MODEL 2452: 6-CUFT BLAST **MACHINE WITH 1.25" PIPING AND** 150 PSI

3

Description	Stock#	Wt.	
Without remotes: with FSV abrasive			
metering valve	01189	430	
 With TLR 300 remotes: and FSV abrasive metering valve 	01187	490	
and Manual Quantum abrasive metering valve		480	
and Auto Quantum abrasive			
metering valve with ACS	21068	500	
SYSTEMS			
2452-300-CA	00916	553	
Includes: 1.25" piping, Blast machine 01187, Apollo 600 HP DLX (for use with compressed air) respirator with Clem-Cool Air Conditioner (CCAC), 50' respirator hose, CPF 20 Breath- ing-air filter and Accessory Package			
2452-ACS-CA	23910	558	
Includes: 1 25" nining Blast machine 21062			

Includes: 1.25" piping, Blast machine 21062, Apollo 600 HP DLX respirator with Clem-Cool Air Conditioner (CCAC), 50' respirator hose, CPF 20 Breathing-air filter and Accessory Package

Includes: 1.25" piping, Blast machine 01187,

Apollo 600 LP DLX (for use with ambient air) respirator with Constant Flow Connector (CFC), 50' respirator hose, and Accessory Package. CAP ambient air pump is an option.

12

ACCESSORY PACKAGE

AUDEOUUTI FAUNAGE	
• Complete accessory package22553	
• 1.5" Air filter w/manual drain22363	8
 50' x 1.25" Supa hose 	
w/NHP-2 and CQPS-223481	42
• Blast hose safety cable15013	1.5
• TXP-6 nozzle	2
• Blast machine screen, 24"03100	10
• Poly all-weather cover15143	3
• Leather gloves, 1 pair02243	.5
• Nylon ties, 8 each02195	<.5
• CQGP-3 gaskets, 10 pk08853	.5
• NW-32 nozzle washers, 10 pk91026	<.5
• Abrasive trap screens, (6)02012	<.5
• Helmet outer lenses, 25 pk04361	1
OPTIONS/ACCESSORIES	
• Blast machine cover, 24"02336	12
Manual Quantum	
abrasive metering valve	9
Carbon monoxide alarm,	
CMS-4 pkg29765	4
Ambient Air Pumps	
-CALIPSO, sgl operator25908	73
-CAP-4, 4 operators w/frame22530	175
-CAP-4C 4 operators $w/cart = 22384$	205

- 2 9 4 73 75
- -CAP-4C, 4 operators w/cart 22384 205

ISO 9001 certified. Clemco is committed to continuous product improvement. Specifications are subject to change without notice. CLEMCO ©2020 Clemco Industries Corp. • One Cable Car Drive • Washington, MO 63090 • Phone: 636.239.4300 • Fax: 800.726.7559

info@clemcoindustries.com · www.clemcoindustries.com

۲

()

